

XTRABOND®50

SILICONIZED ACRYLIC SEALANT



XtraBond®50 is a premium grade multi-purpose siliconized acrylic latex sealant. The product is engineered to provide excellent adhesion to vinyl, aluminum, wood, sheet metal & most common building materials without need of a primer. The addition of a silicone polymer provides greater flexibility than other latex products.

XtraBond®50 is ideal for use in the installation of windows & doors – as well as interior sealing of cultured marble and tile. Installers prefer it, because the product cures rapidly to form a durable tight bond.

FEATURES

- Window & Door Approved
- Cleans Up with Water
- Excellent Flexibility
- Mildew Resistant
- Quick Curing
- Paintable

APPLICATIONS

- General Construction
- Window & Door
- Kitchen & Bath

Green Advantage Program

This XtraBond® product is a part of Premier's "Green Advantage" Program – the designation of our commitment to not only superior products & services, but also the environment. Our engineering formulations, manufacturing standards and production practices allow us to be a leader in the supply of eco-friendly and VOC compliant products. Learn more at www.PremierBuildingSolutions.net/green



Weather Defense System

This XtraBond® product is a part of the XtraGuard Weather Defense System™, an integrated product line of building components developed from advanced materials research that increase the durability and comfort of residential and commercial structures by effectively managing moisture. The product's aggressive adhesion and compatibility with all major building materials makes it a critical link in the XtraGuard Weather Defense System, when combined with the company's complete line of Wraps and Flashing Products.



Who is Premier?

This XtraBond® product is manufactured and distributed by Premier Building Solutions, a manufacturer of high performance systems that provide protection in commercial and residential buildings – as well as a variety of other industrial and transportation applications.

The company's history of innovation has led to the development of breakthrough adhesive chemistries and new industrial-strength products that help customers increase the efficiency and durability of their critical assets.



PREMIER BUILDING SOLUTIONS, INC
866-512-GLUE (4583) • Massillon, OH
www.PremierBuildingSolutions.net





XTRABOND[®]50

SILICONIZED ACRYLIC SEALANT

PROPERTIES:

Cure Rate	1/4" Bead per 24 Hrs
VOC	0.0751 lb/gal
Elongation @ Break	1200%
Shore A	25 +/- 5
Movement Capability	25%
Lap Shear	550 psi
Staining	None
Sag	None

SPECIFICATIONS: XTraBond®50 meets or exceeds ASTM C834.

COLORS: This product is offered in hundreds of colors using our Custom Color Matching & Mixing System. For current color offerings, please visit our website: www.premierbuildingsolutions.net/color/

SURFACE PREPARATIONS: The substrate must be clean, frost free and free of any oils, greases or incompatible sealers that may interfere with adhesion. Do not apply if surface is contaminated. It is recommended to test all substrates prior to applications.

DIRECTIONS: For best results, prepare clean surface. Cut nozzle to desired bead size. Apply with caulking gun, forcing sealant onto the substrate, then tool if needed. Clean excess material with water.

STORAGE: Material is to be stored under controlled dry environment (below 75° F). Use within 12 months from date of manufacture. For best results, keep material in tightly closed containers when not in use. Do not freeze.

PACKAGING



CARTRIDGES

LIMITED LIFETIME WARRANTY: This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Building Solutions, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.

Premier Building Solutions specifically disclaims and makes no warranties, express or implied, about this product, its merchantability, or its fitness for a particular purpose. All recommendations, directions, and suggestions for its use are consistent with our testing and research for a variety of applications, but no promises, guarantees, or warranties are being made with regard to its use, whether or not consistent with the directions, or its effectiveness for any given application. Users of this product should do so in compliance with all applicable laws and regulations. User of this product should conduct its own field test, to assure results.

131120-PBS-XB50-Ver4