

# Safety Data Sheet

## MasterSeal NP 1 Off White

Revision date : 2020/04/23  
Version: 5.0

Page: 1/12  
(30630245/SDS\_GEN\_US/EN)

### 1. Identification

#### Product identifier used on the label

## MasterSeal NP 1 Off White

#### Recommended use of the chemical and restriction on use

Recommended use\*: Product for construction chemicals  
Recommended use\*: for industrial and professional users

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

#### Details of the supplier of the safety data sheet

Company:

BASF CORPORATION  
100 Park Avenue  
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

#### Emergency telephone number

CHEMTREC: 1-800-424-9300  
BASF HOTLINE: 1-800-832-HELP (4357)

#### Other means of identification

Chemical family: sealant

---

### 2. Hazards Identification

**According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200**

#### Classification of the product

Eye Dam./Irrit.	2A	Serious eye damage/eye irritation
Resp. Sens.	1	Respiratory sensitization
Skin Sens.	1	Skin sensitization
Carc.	2	Carcinogenicity
STOT RE	1	Specific target organ toxicity — repeated exposure
Acute Tox.	4 (Inhalation - vapour)	Acute toxicity

# Safety Data Sheet

## MasterSeal NP 1 Off White

Revision date : 2020/04/23  
Version: 5.0

Page: 2/12  
(30630245/SDS\_GEN\_US/EN)

### Label elements

Pictogram:



Signal Word:  
Danger

Hazard Statement:

H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H372	Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P271	Use only outdoors or in a well-ventilated area.
P260	Do not breathe dust/gas/mist/vapours.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P284	In case of inadequate ventilation wear respiratory protection.
P270	Do not eat, drink or smoke when using this product.
P264	Wash contaminated body parts thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary Statements (Response):

P308 + P311	IF exposed or concerned: Call a POISON CENTER or physician.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P314	Get medical advice/attention if you feel unwell.
P303 + P352	IF ON SKIN (or hair): Wash with plenty of soap and water.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P337 + P311	If eye irritation persists: Call a POISON CENTER or physician.

Precautionary Statements (Storage):

P405	Store locked up.
------	------------------

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

### Hazards not otherwise classified

No applicable information available.

Labeling of special preparations (GHS):

# Safety Data Sheet

## MasterSeal NP 1 Off White

Revision date : 2020/04/23

Version: 5.0

Page: 3/12

(30630245/SDS\_GEN\_US/EN)

Restricted to professional users.

CONTAINS ISOCYANATES. INHALATION OF ISOCYANATE MISTS OR VAPORS MAY CAUSE RESPIRATORY IRRITATION, BREATHLESSNESS, CHEST DISCOMFORT AND REDUCED PULMONARY FUNCTION. OVEREXPOSURE WELL ABOVE THE PEL MAY RESULT IN BRONCHITIS, BRONCHIAL SPASMS AND PULMONARY EDEMA. LONG-TERM EXPOSURE TO ISOCYANATES HAS BEEN REPORTED TO CAUSE LUNG DAMAGE, INCLUDING REDUCED LUNG FUNCTION WHICH MAY BE PERMANENT. ACUTE OR CHRONIC OVEREXPOSURE TO ISOCYANATES MAY CAUSE SENSITIZATION IN SOME INDIVIDUALS, RESULTING IN ALLERGIC RESPIRATORY REACTIONS INCLUDING WHEEZING, SHORTNESS OF BREATH AND DIFFICULTY BREATHING. ANIMAL TESTS INDICATE THAT SKIN CONTACT MAY PLAY A ROLE IN CAUSING RESPIRATORY SENSITIZATION.

### 3. Composition / Information on Ingredients

#### According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Stoddard solvent

CAS Number: 8052-41-3

Content (W/W):  $\geq 1.0 - < 3.0\%$

Synonym: No data available.

calcium oxide

CAS Number: 1305-78-8

Content (W/W):  $\geq 1.0 - < 3.0\%$

Synonym: Calcium oxide

Carbamic acid, 1,6-hexanediybis-, bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] ester

CAS Number: 59719-67-4

Content (W/W):  $\geq 1.0 - < 3.0\%$

Synonym: No data available.

toluene-2,6-diisocyanate

CAS Number: 91-08-7

Content (W/W):  $\geq 0.3 - < 1.0\%$

Synonym: 1,3-Diisocyanato-2-methylbenzene

trimethoxy(3-(oxiranylmethoxy)propyl)silane

CAS Number: 2530-83-8

Content (W/W):  $\geq 0.3 - < 1.0\%$

Synonym: Trimethoxy[3-(oxiranylmethoxy)propyl]silane; (3-Glycidoxypropyl)trimethoxysilane

Limestone

CAS Number: 1317-65-3

Content (W/W):  $\geq 15.0 - < 20.0\%$

Synonym: No data available.

Titanium dioxide

CAS Number: 13463-67-7

Content (W/W):  $\geq 0.0 - < 10.0\%$

Synonym: C.I. Pigment White 6

talc

CAS Number: 14807-96-6

Content (W/W):  $\geq 3.0 - < 5.0\%$

Synonym: hydrated magnesium silicate

# Safety Data Sheet

## MasterSeal NP 1 Off White

Revision date : 2020/04/23  
Version: 5.0

Page: 4/12  
(30630245/SDS\_GEN\_US/EN)

---

### 4. First-Aid Measures

#### Description of first aid measures

**General advice:**

Remove contaminated clothing.

**If inhaled:**

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required.

**If on skin:**

Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

**If in eyes:**

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. Immediate medical attention required.

**If swallowed:**

Rinse mouth and then drink 200-300 ml of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediate medical attention required.

#### Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Hazards: Symptoms can appear later.

#### Indication of any immediate medical attention and special treatment needed

Note to physician

Antidote:

Specific antidotes or neutralizers to isocyanates do not exist.

Treatment:

Treatment should be supportive and based on the judgement of the physician in response to the reaction of the patient.

---

### 5. Fire-Fighting Measures

#### Extinguishing media

Suitable extinguishing media:

foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:

water jet

#### Special hazards arising from the substance or mixture

Hazards during fire-fighting:

nitrous gases, fumes/smoke, isocyanate, vapour

#### Advice for fire-fighters

# Safety Data Sheet

## MasterSeal NP 1 Off White

Revision date : 2020/04/23

Version: 5.0

Page: 5/12

(30630245/SDS\_GEN\_US/EN)

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

### Further information:

Keep containers cool by spraying with water if exposed to fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

---

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment.

### Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

### Methods and material for containment and cleaning up

For small amounts: Absorb isocyanate with suitable absorbent material (see § 40 CFR, sections 260, 264 and 265 for further information). Shovel into open container. Do not make container pressure tight. Move container to a well-ventilated area (outside). Spill area can be decontaminated with the following recommended decontamination solution: Mixture of 90 % water, 5-8 % household ammonia, 2-5 % detergent. Add at a 10 to 1 ratio. Allow to stand for at least 48 hours to allow escape of evolved carbon dioxide.

For large amounts: If temporary control of isocyanate vapor is required, a blanket of protein foam or other suitable foam (available from most fire departments) may be placed over the spill. Transfer as much liquid as possible via pump or vacuum device into closed but not sealed containers for disposal.

For residues: The following measures should be taken for final cleanup: Wash down spill area with decontamination solution. Allow solution to stand for at least 10 minutes.

Dike spillage.

---

## 7. Handling and Storage

### Precautions for safe handling

Provide suitable exhaust ventilation at the processing machines. Ensure thorough ventilation of stores and work areas. Avoid aerosol formation. When handling heated product, vapours of the product should be ventilated, and respiratory protection used. Wear respiratory protection when spraying. Danger of bursting when sealed gastight. Protect against moisture. If bulging of drum occurs, transfer to well ventilated area, puncture to relieve pressure, open vent and let stand for 48 hours before resealing.

Protection against fire and explosion:

The product is neither self-ignitable, nor an explosion hazard, nor does it promote fires.

### Conditions for safe storage, including any incompatibilities

Observe VCI storage rules.

Further information on storage conditions: Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight.

Storage stability:

Storage temperature: 5 - 32 °C

Protect from temperatures below: -17 °C

Protect from temperatures above: 48 °C

# Safety Data Sheet

## MasterSeal NP 1 Off White

Revision date : 2020/04/23  
Version: 5.0

Page: 6/12  
(30630245/SDS\_GEN\_US/EN)

### 8. Exposure Controls/Personal Protection

#### Components with occupational exposure limits

toluene-2,6-diisocyanate	ACGIH TLV	STEL value 0.005 ppm Inhalable fraction and vapor ; Skin Designation Inhalable fraction and vapor ; The substance can be absorbed through the skin. TWA value 0.001 ppm Inhalable fraction and vapor ; Skin Designation Inhalable fraction and vapor ; Danger of cutaneous absorption
calcium oxide	OSHA PEL ACGIH TLV	PEL 5 mg/m3 ; TWA value 5 mg/m3 ; TWA value 2 mg/m3 ;
Limestone	OSHA PEL	PEL 5 mg/m3 Respirable fraction ; PEL 15 mg/m3 Total dust ; TWA value 5 mg/m3 Respirable fraction ; TWA value 15 mg/m3 Total dust ;
Titanium dioxide	OSHA PEL ACGIH TLV	PEL 15 mg/m3 Total dust ; TWA value 10 mg/m3 Total dust ; TWA value 10 mg/m3 ;
talc	ACGIH TLV	TWA value 2 mg/m3 Respirable fraction ; The value is for particulate matter containing no asbestos and <1% crystalline silica.
Stoddard solvent	OSHA PEL ACGIH TLV	PEL 500 ppm 2,900 mg/m3 ; TWA value 100 ppm 525 mg/m3 ; TWA value 100 ppm ;

#### **Advice on system design:**

No applicable information available.

#### **Personal protective equipment**

##### **Respiratory protection:**

When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators. When atmospheric levels may exceed the occupational exposure limit (PEL or TLV) NIOSH-certified air-purifying respirators equipped with an organic vapor sorbent and particulate filter can be used as long as appropriate precautions and change out schedules are in place. For emergency or non-routine, high exposure situations, including confined space entry, use a NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied-air respirator (SAR) with escape provisions.

##### **Hand protection:**

Chemical resistant protective gloves should be worn to prevent all skin contact., Suitable materials may include, chloroprene rubber (Neoprene), nitrile rubber (Buna N), chlorinated polyethylene, polyvinylchloride (Pylox), butyl rubber, depending upon conditions of use.

# Safety Data Sheet

## MasterSeal NP 1 Off White

Revision date : 2020/04/23

Version: 5.0

Page: 7/12

(30630245/SDS\_GEN\_US/EN)

### Eye protection:

Tightly fitting safety goggles (chemical goggles). Wear face shield if splashing hazard exists.

### Body protection:

Cover as much of the exposed skin as possible to prevent all skin contact., Suitable materials may include, saran-coated material, depending upon conditions of use.

### General safety and hygiene measures:

Wear protective clothing as necessary to prevent contact. Eye wash fountains and safety showers must be easily accessible. Observe the appropriate PEL or TLV value. Wash soiled clothing immediately. Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.

## 9. Physical and Chemical Properties

Form:	paste	
Odour:	mild	
Odour threshold:	No applicable information available.	
Colour:	off-white	
pH value:	The product has not been tested.	
Melting point:	No applicable information available.	
Boiling point:	No applicable information available.	
Sublimation point:	No applicable information available.	
Flash point:	Non-flammable.	
Flammability:	not flammable	(UN Test N.1 (ready combustible solids))
Lower explosion limit:	No applicable information available.	
Upper explosion limit:	No applicable information available.	
Autoignition:	No applicable information available.	
Vapour pressure:	No applicable information available.	
Density:	10.1 lb/USg ( 25 °C)	
Relative density:	No applicable information available.	
Vapour density:	No applicable information available.	
Partitioning coefficient n-octanol/water (log Pow):	No applicable information available.	
Self-ignition temperature:	not self-igniting	
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
Viscosity, dynamic:	No applicable information available.	
Viscosity, kinematic:	No applicable information available.	
Solubility in water:	( 15 °C) insoluble	
Miscibility with water:	( 15 °C) not (e.g. <10%)	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Evaporation rate:	No applicable information available.	
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.	

## 10. Stability and Reactivity

### Reactivity

# Safety Data Sheet

## MasterSeal NP 1 Off White

Revision date : 2020/04/23

Version: 5.0

Page: 8/12

(30630245/SDS\_GEN\_US/EN)

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties:  
Not an oxidizer.

### Chemical stability

The product is stable if stored and handled as prescribed/indicated.

### Possibility of hazardous reactions

Reacts with water, with formation of carbon dioxide. Risk of bursting. Reacts with alcohols. Reacts with acids. Reacts with alkalis. Reacts with amines. Risk of exothermic reaction. Risk of polymerization. Contact with certain rubbers and plastics can cause brittleness of the substance/product with subsequent loss in strength.

### Conditions to avoid

Avoid moisture.

### Incompatible materials

acids, amines, alcohols, water, Alkalines, strong bases, Substances/products that react with isocyanates.

### Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: carbon monoxide, carbon dioxide, nitrogen oxide, hydrogen cyanide, nitrogen oxides, aromatic isocyanates, gases/vapours

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

---

## 11. Toxicological information

### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

### Acute Toxicity/Effects

#### Acute toxicity

Assessment of acute toxicity: Harmful by inhalation. Inhalation of diisocyanates may cause irritation of the mucous membranes of the nose, throat or trachea, breathlessness, chest discomfort, difficult breathing and reduced pulmonary function. High airborne concentrations may result additionally in eye irritation, headache, chemical bronchitis, asthma-like symptoms or pulmonary edema.

Isocyanates have also been reported to cause hyper-sensitivity pneumonitis, which is characterized by flu-like symptoms, the onset of which may be delayed. Symptoms include nausea, vomiting and abdominal pain.

#### Oral

No applicable information available.

#### Inhalation

Type of value: ATE

Value: 14.8 mg/l

Determined for vapor



# Safety Data Sheet

## MasterSeal NP 1 Off White

Revision date : 2020/04/23

Version: 5.0

Page: 9/12

(30630245/SDS\_GEN\_US/EN)

### Dermal

No applicable information available.

### Assessment other acute effects

No applicable information available.

### Irritation / corrosion

Assessment of irritating effects: Eye contact causes irritation.

### Sensitization

Assessment of sensitization: The substance may cause sensitization of the respiratory tract. Sensitization after skin contact possible.

### Aspiration Hazard

No aspiration hazard expected.

## **Chronic Toxicity/Effects**

### Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated exposure to small quantities may affect certain organs.

### Genetic toxicity

Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

### Carcinogenicity

Assessment of carcinogenicity: Contains a compound classified as IARC Group 2B (possibly carcinogenic to humans).

*Information on: toluene-2,6-diisocyanate*

*Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests.*

*Information on: Titanium dioxide*

*Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term studies in rats in which the substance was given by inhalation, a carcinogenic effect was observed. Tumors were only observed in rats after chronic inhalative exposure to high concentrations which caused sustained lung inflammation. In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. Dermal exposure is not expected to be carcinogenic.*

-----

### Reproductive toxicity

Assessment of reproduction toxicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

### Teratogenicity

Assessment of teratogenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

### Other Information

The product has not been tested. The statement has been derived from the properties of the individual components.

# Safety Data Sheet

## MasterSeal NP 1 Off White

Revision date : 2020/04/23  
Version: 5.0

Page: 10/12  
(30630245/SDS\_GEN\_US/EN)

---

### 12. Ecological Information

#### Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Based on available Data, the classification criteria are not met. There is a high probability that the product is not acutely harmful to aquatic organisms.

#### Persistence and degradability

Assessment biodegradation and elimination (H<sub>2</sub>O)

Not readily biodegradable (by OECD criteria).

#### Bioaccumulative potential

Assessment bioaccumulation potential

Discharge into the environment must be avoided.

#### Mobility in soil

Assessment transport between environmental compartments

No data available.

#### Additional information

Other ecotoxicological advice:

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

---

### 13. Disposal considerations

#### Waste disposal of substance:

Observe national and local legal requirements. Disposal requirements are dependent on the hazard classification and will vary by location and the type of disposal selected. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. Residues should be disposed of in the same manner as the substance/product.

#### Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned. Packs that cannot be cleaned should be disposed of in the same manner as the contents.

---

### 14. Transport Information

#### Land transport

USDOT

Not classified as a dangerous good under transport regulations

#### Sea transport

IMDG

Not classified as a dangerous good under transport regulations

# Safety Data Sheet

## MasterSeal NP 1 Off White

Revision date : 2020/04/23  
Version: 5.0

Page: 11/12  
(30630245/SDS\_GEN\_US/EN)

**Air transport**  
IATA/ICAO

Not classified as a dangerous good under transport regulations

### 15. Regulatory Information

#### Federal Regulations

**Registration status:**

Chemical TSCA, US released / listed

TSCA § 5(a) proposed Significant New Use Restriction (SNUR)  
This product contains a substance subject to a pending SNUR.  
40 CFR 721.10789

**EPCRA 311/312 (Hazard categories):** Refer to SDS section 2 for GHS hazard classes applicable for this product.

**EPCRA 313:**

CAS Number

91-08-7

Chemical name

toluene-2,6-diisocyanate

CERCLA RQ

100 LBS

CAS Number

91-08-7

Chemical name

toluene-2,6-diisocyanate

#### State regulations

State RTK

PA

CAS Number

1305-78-8

Chemical name

calcium oxide

1317-65-3

Limestone

13463-67-7

Titanium dioxide

14807-96-6

talc

8052-41-3

Stoddard solvent

584-84-9

toluene-2,4-diisocyanate

NJ

1305-78-8

calcium oxide

1317-65-3

Limestone

13463-67-7

Titanium dioxide

14807-96-6

talc

8052-41-3

Stoddard solvent

91-08-7

toluene-2,6-diisocyanate

#### **Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:**

**WARNING:** This product can expose you to chemicals including TITANIUM DIOXIDE (AIRBORNE, UNBOUND PARTICLES OF RESPIRABLE SIZE), which is known to the State of California to cause cancer, and METHANOL, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**NFPA Hazard codes:**

Health: 2

Fire: 1

Reactivity: 0

Special:

# Safety Data Sheet

## MasterSeal NP 1 Off White

Revision date : 2020/04/23  
Version: 5.0

Page: 12/12  
(30630245/SDS\_GEN\_US/EN)

---

### 16. Other Information

**SDS Prepared by:**  
BASF NA Product Regulations  
SDS Prepared on: 2020/04/23

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

---

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.  
END OF DATA SHEET