

Safety Data Sheet

MasterSeal NP 150 Off Wht

Revision date : 2018/05/23
Version: 4.0

Page: 1/10
(30605760/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

MasterSeal NP 150 Off Wht

Recommended use of the chemical and restriction on use

Recommended use*: for industrial and professional users

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: sealant

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Eye Dam./Irrit.	2A	Serious eye damage/eye irritation
Skin Sens.	1	Skin sensitization
Repr.	1B (fertility)	Reproductive toxicity
Repr.	1B (unborn child)	Reproductive toxicity
STOT RE	2	Specific target organ toxicity — repeated exposure
Aquatic Acute	3	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic

Safety Data Sheet

MasterSeal NP 150 Off Wht

Revision date : 2018/05/23
Version: 4.0

Page: 2/10
(30605760/SDS_GEN_US/EN)

Label elements

Pictogram:



Signal Word:
Danger

Hazard Statement:

H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H373	May cause damage to organs (Liver, Kidney) through prolonged or repeated exposure.
H360	May damage fertility. May damage the unborn child.
H402	Harmful to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P260	Do not breathe dust/gas/mist/vapours.
P273	Avoid release to the environment.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P272	Contaminated work clothing should not be allowed out of the workplace.
P264	Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314	Get medical advice/attention if you feel unwell.
P303 + P362	IF ON SKIN (or hair): Wash with plenty of soap and water.
P308 + P311	IF exposed or concerned: Call a POISON CENTER or doctor/physician.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P337 + P311	If eye irritation persists: Call a POISON CENTER or doctor/physician.

Precautionary Statements (Storage):

P405	Store locked up.
------	------------------

Precautionary Statements (Disposal):

P501	Dispose of contents/container to hazardous or special waste collection point.
------	---

Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
-------------------	-----------------	----------------------

Safety Data Sheet

MasterSeal NP 150 Off Wht

Revision date : 2018/05/23

Version: 4.0

Page: 3/10

(30605760/SDS_GEN_US/EN)

471-34-1	>= 20.0 - < 50.0%	Calcium carbonate
1317-65-3	>= 3.0 - < 7.0%	Limestone
13463-67-7	>= 3.0 - < 10.0%	Titanium dioxide
57-11-4	>= 0.3 - < 3.0%	stearic acid
1760-24-3	>= 0.3 - < 1.0%	1,2-Ethanediamine, N-[3-(trimethoxysilyl)propyl]-
22673-19-4	>= 0.1 - < 0.2%	Tin, dibutylbis(2,4-pentanedionato-.kappa.O2,.kappa.O4)-, (OC-6-11)-
25973-55-1	>= 0.2 - <= 1.0%	2-(2H-Benzotriazol-2-yl)-4,6-ditertpentylphenol
52829-07-9	>= 0.2 - <= 1.0%	bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate

4. First-Aid Measures

Description of first aid measures

General advice:

First aid personnel should pay attention to their own safety. Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

No applicable information available.

If on skin:

Wash thoroughly with soap and water. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Rinse mouth and then drink plenty of water. Do not induce vomiting.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Hazards: No applicable information available.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:

foam, water spray, dry powder, carbon dioxide

Safety Data Sheet

MasterSeal NP 150 Off Wht

Revision date : 2018/05/23
Version: 4.0

Page: 4/10
(30605760/SDS_GEN_US/EN)

Unsuitable extinguishing media for safety reasons:
water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
carbon dioxide, carbon monoxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

Advice for fire-fighters

Protective equipment for fire-fighting:
Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Sweep/shovel up. Dispose of absorbed material in accordance with regulations.
For large amounts: Sweep/shovel up. Dispose of absorbed material in accordance with regulations.

7. Handling and Storage

Precautions for safe handling

Avoid contact with the skin, eyes and clothing.

Protection against fire and explosion:

Keep away from sources of ignition - No smoking. The relevant fire protection measures should be noted.

Conditions for safe storage, including any incompatibilities

Observe VCI storage rules.

Suitable materials for containers: tinned carbon steel (Tinplate)

Further information on storage conditions: Keep only in the original container in a cool, well-ventilated place. Protect from direct sunlight. Store protected against freezing.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

stearic acid

ACGIH TLV TWA value 10 mg/m³ Inhalable fraction ; TWA
value 3 mg/m³ Respirable fraction ;

Safety Data Sheet

MasterSeal NP 150 Off Wht

Revision date : 2018/05/23
Version: 4.0

Page: 5/10
(30605760/SDS_GEN_US/EN)

Calcium carbonate	OSHA PEL	PEL 5 mg/m3 Respirable fraction ; PEL 15 mg/m3 Total dust ; TWA value 5 mg/m3 Respirable fraction ; TWA value 15 mg/m3 Total dust ;
Limestone	OSHA PEL	PEL 5 mg/m3 Respirable fraction ; PEL 15 mg/m3 Total dust ; TWA value 5 mg/m3 Respirable fraction ; TWA value 15 mg/m3 Total dust ;
Titanium dioxide	OSHA PEL ACGIH TLV	PEL 15 mg/m3 Total dust ; TWA value 10 mg/m3 Total dust ; TWA value 10 mg/m3 ;

Advice on system design:

No applicable information available.

Personal protective equipment

Respiratory protection:

Wear appropriate certified respirator when exposure limits may be exceeded.

Hand protection:

Chemical resistant protective gloves

Eye protection:

Safety glasses with side-shields.

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Avoid contact with the skin, eyes and clothing. No special measures necessary if stored and handled correctly. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

9. Physical and Chemical Properties

Form:	paste
Odour:	odourless
Odour threshold:	No applicable information available.
Colour:	pigmented
pH value:	neutral to slightly alkaline
Melting point:	No applicable information available.
Boiling point:	No applicable information available.
Sublimation point:	No applicable information available.
Flash point:	Non-flammable.
Flammability:	not determined
Lower explosion limit:	No applicable information available.
Upper explosion limit:	No applicable information available.

Safety Data Sheet

MasterSeal NP 150 Off Wht

Revision date : 2018/05/23
Version: 4.0

Page: 6/10
(30605760/SDS_GEN_US/EN)

Autoignition:	No data available.
Vapour pressure:	No applicable information available.
Density:	12.2 lb/USg (73 - 77 °F)
Relative density:	No applicable information available.
Bulk density:	approx. 1.5 g/cm ³
Vapour density:	Heavier than air.
Partitioning coefficient n-octanol/water (log Pow):	No data available.
Self-ignition temperature:	not self-igniting
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.
Viscosity, dynamic:	No applicable information available.
Viscosity, kinematic:	No applicable information available.
Solubility in water:	slightly soluble
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	No applicable information available.
Evaporation rate:	No applicable information available.
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid

See MSDS section 7 - Handling and storage.

Incompatible materials

strong acids, strong bases, strong oxidizing agents, strong reducing agents

Hazardous decomposition products

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Safety Data Sheet

MasterSeal NP 150 Off Wht

Revision date : 2018/05/23
Version: 4.0

Page: 7/10
(30605760/SDS_GEN_US/EN)

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Based on available Data, the classification criteria are not met.

Oral

No applicable information available.

Inhalation

No applicable information available.

Dermal

No applicable information available.

Assessment other acute effects

No applicable information available.

Irritation / corrosion

Assessment of irritating effects: Irritating to eyes. The product has not been tested. The statement has been derived from the properties of the individual components.

Sensitization

Assessment of sensitization: Contains a known or suspected skin sensitizer.

Information on: 1,2-Ethanediamine, N-[3-(trimethoxysilyl)propyl]-

Guinea pig maximization test

Species: guinea pig

Result: Caused skin sensitization in animal studies.

Method: Directive 84/449/EEC, B.6

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: No reliable data was available concerning repeated dose toxicity. Based on available Data, the classification criteria are not met.

Genetic toxicity

Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Information on: Titanium dioxide

Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term studies in rats in which the substance was given by inhalation, a carcinogenic effect was observed. Tumors were only observed in rats after chronic inhalative exposure to high concentrations which caused

Safety Data Sheet

MasterSeal NP 150 Off Wht

Revision date : 2018/05/23
Version: 4.0

Page: 8/10
(30605760/SDS_GEN_US/EN)

sustained lung inflammation. In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. Dermal exposure is not expected to be carcinogenic.

Reproductive toxicity

Assessment of reproduction toxicity: Contains a reproductive toxin.

*Information on: Tin, dibutylbis(2,4-pentanedionato-.kappa.O2,.kappa.O4)-, (OC-6-11)-
Assessment of reproduction toxicity: Causes impairment of fertility in laboratory animals. The results were determined in a Screening test (OECD 421/422). The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

Teratogenicity

Assessment of teratogenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Persistence and degradability

Assessment biodegradation and elimination (H₂O)

Inherently biodegradable. The insoluble fraction can be removed by mechanical means in suitable waste water treatment plants.

The polymer component of the product is poorly biodegradable.

Bioaccumulative potential

Assessment bioaccumulation potential

Discharge into the environment must be avoided.

Mobility in soil

Assessment transport between environmental compartments

No data available.

Additional information

Safety Data Sheet

MasterSeal NP 150 Off Wht

Revision date : 2018/05/23
Version: 4.0

Page: 9/10
(30605760/SDS_GEN_US/EN)

Other ecotoxicological advice:

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with local authority regulations. Do not discharge into drains/surface waters/groundwater.

14. Transport Information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

State regulations

State RTK

PA

CAS Number

471-34-1

1317-65-3

13463-67-7

28553-12-0

68515-48-0

Chemical name

Calcium carbonate

Limestone

Titanium dioxide

Di-isononylphthalate

1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich

NJ

1317-65-3

13463-67-7

Limestone

Titanium dioxide

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

Safety Data Sheet

MasterSeal NP 150 Off Wht

Revision date : 2018/05/23
Version: 4.0

Page: 10/10
(30605760/SDS_GEN_US/EN)

WARNING: This product can expose you to chemicals including LEAD, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

NFPA Hazard codes:

Health: 2 Fire: 0 Reactivity: 0 Special:

16. Other Information

SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2018/05/23

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET