

SAFETY DATA SHEET

THE DOW CHEMICAL COMPANY

Product name: DOWSIL™ 1199 Silicone Glazing Sealant, Issue Date: 08/30/2019

Bronze

Print Date: 08/31/2019

THE DOW CHEMICAL COMPANY encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: DOWSIL™ 1199 Silicone Glazing Sealant, Bronze

Recommended use of the chemical and restrictions on use

Identified uses: Adhesive, binding agents

COMPANY IDENTIFICATION

THE DOW CHEMICAL COMPANY 2030 DOW CENTER MIDLAND MI 48674-0000 UNITED STATES

Customer Information Number: 800-258-2436

SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: CHEMTREC +1 800-424-9300

Local Emergency Contact: 800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

GHS classification in accordance with 29 CFR 1910.1200
Eye irritation - Category 2A
Skin sensitisation - Category 1
Reproductive toxicity - Category 2
Specific target organ toxicity - repeated exposure - Category 2 - Oral

Specific target organ toxicity - repeated exposure - Category 2 - Inhalation

Label elements Hazard pictograms





Signal word: WARNING!

Hazards

May cause an allergic skin reaction.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

May cause damage to organs (Blood) through prolonged or repeated exposure if swallowed.

May cause damage to organs (Respiratory Tract) through prolonged or repeated exposure if inhaled.

Precautionary statements

Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/ attention.

If skin irritation or rash occurs: Get medical advice/ attention.

If eye irritation persists: Get medical advice/ attention.

Wash contaminated clothing before reuse.

Storage

Store locked up.

Disposal

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Silicone elastomer

This product is a mixture.

Component	CASRN	Concentration
2-Butanone, O,O',O"- (methylsilylidyne)trioxime	22984-54-9	>= 3.0 - <= 4.0 %
Vinyltri (methylethylketoxime) silane	2224-33-1	>= 1.4 - <= 1.5 %

Page 2 of 17

N-(3-(Trimethoxysilyl) propyl)-1,2- ethanediamine	1760-24-3	>= 1.0 - <= 1.1 %
Octamethyl Cyclotetrasiloxane	556-67-2	>= 0.38 - <= 0.4 %
Methyltri(ethylmethylketoxime)silane isomers and oligomers	Not available	>= 0.35 - <= 0.36 %
Bis[(2-ethyl-2,5-dimethyl)stannane	68928-76-7	>= 0.19 - <= 0.2 %

4. FIRST AID MEASURES

Description of first aid measures General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Skin contact: Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands.

Eye contact: Immediately flush eyes with water; remove contact lenses, if present, after the first 5 minutes, then continue flushing eyes for at least 15 minutes. Obtain medical attention without delay, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

Ingestion: No emergency medical treatment necessary.

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIREFIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Water spray. Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical.

Unsuitable extinguishing media: None known...

Page 3 of 17

Special hazards arising from the substance or mixture

Hazardous combustion products: Carbon oxides. Silicon oxides. Nitrogen oxides (NOx).

Unusual Fire and Explosion Hazards: Exposure to combustion products may be a hazard to health..

Advice for firefighters

Fire Fighting Procedures: Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations..

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus.. Use personal protective equipment..

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions: Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up: Wipe up or scrape up and contain for salvage or disposal. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, Sections 13 and 15 of this SDS provide information regarding certain local or national requirements. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur. See sections: 7, 8, 11, 12 and 13.

7. HANDLING AND STORAGE

Precautions for safe handling: Do not get on skin or clothing. Do not swallow. Do not get in eyes. Protect from moisture. Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice. Use only with adequate ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Conditions for safe storage: Keep in properly labelled containers. Store locked up. Store in accordance with the particular national regulations.

Do not store with the following product types: Strong oxidizing agents. Unsuitable materials for containers: Do not store in or use iron or steel containers.

Page 4 of 17

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
Octamethyl	US WEEL	TWA	10 ppm
Cyclotetrasiloxane			
Bis[(2-ethyl-2,5-	OSHA Z-1	TWA	0.1 mg/m3 , Tin
dimethylhexanoyl)oxy](dimet			9
hyl)stannane			
	ACGIH	TWA	0.1 mg/m3 , Tin
	Upper Respiratory Tract irri	I nervous system; immune el tation; headache: Headache classifiable as a human carcir es: varies	ff: Immune effects; URT irr: ; eye irr: Eye irritation;
	ACGIH	STEL	0.2 mg/m3 , Tin
	Upper Respiratory Tract irri		; eye irr: Eye irritation;
	OSHA P0	TWA	0.1 mg/m3 , Tin
	Further information: X: Skin		
	NIOSH REL	TWA	0.1 mg/m3 , Tin
	Further information: Also se absorption	ee specific listing for Cyhexati	n.; skin: Potential for dermal
Methyl Ethyl Ketoxime	Dow IHG	TWA	0.15 ppm
	Further information: Skin Sc		
	US WEEL	TWA	10 ppm
		Dermal Sensitization Notation	
Methanol	ACGIH	TWA	200 ppm
	eye dam: Eye damage; BE	che: Headache; nausea: Nau II: Substances for which there section); Skin: Danger of cu	is a Biological Exposure
	ACGIH	STEL	250 ppm
	eye dam: Eye damage; BE	che: Headache; nausea: Nau II: Substances for which there section); Skin: Danger of cu	e is a Biological Exposure
	OSHA Z-1	TWA	260 mg/m3 200 ppm
		e value in mg/m3 is approxim	
	OSHA P0	STEL	325 mg/m3 250 ppm
	Further information: X: Skin		
	OSHA P0	TWA	260 mg/m3 200 ppm
	Further information: X: Skin	notation	

The following substance(s), which have Occupational Exposure Limit(s) (OEL), may be formed during handling or processing:

Methyl ethyl ketoxime Methanol.

Biological occupational exposure limits

_biological occupational exposure innits						
Components	CAS-No.	Control	_		Permissible	Basis
		parameters	specimen	time	concentration	
Methanol	67-56-1	Methanol	Urine	End of	15 mg/l	ACGIH
				shift (As		BEI

soon as possible after exposure ceases) Issue Date: 08/30/2019

Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use chemical goggles.

Skin protection

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Butyl rubber. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. Examples of acceptable glove barrier materials include: Natural rubber ("latex"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use an approved respirator. When respiratory protection is required, use an approved positive-pressure self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state paste

Color in accordance with the product description

Odor slight

Odor Threshold

pH

Not applicable

Melting point/range

No data available

Not applicable

Flash point

Not applicable

Not applicable

Evaporation Rate (Butyl Acetate

Not applicable

= 1)

Flammability (solid, gas) Not classified as a flammability hazard

Lower explosion limitNo data availableUpper explosion limitNo data availableVapor PressureNot applicableRelative Vapor Density (air = 1)No data available

Relative Density (water = 1) 1.04

Water solubility

Partition coefficient: n
No data available

No data available

octanol/water

Auto-ignition temperatureNo data availableDecomposition temperatureNo data availableDynamic ViscosityNot applicableKinematic ViscosityNot applicableExplosive propertiesNot explosive

Oxidizing properties The substance or mixture is not classified as oxidizing.

Molecular weightNo data availableParticle sizeNo data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: Not classified as a reactivity hazard.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Can react with strong oxidizing agents.

Conditions to avoid: Do not expose to temperatures above 212 °F/100 °C. Exposure to moisture

Incompatible materials: Oxidizing agents

Hazardous decomposition products:

Decomposition products can include and are not limited to: Formaldehyde. Methyl Ethyl Ketoxime. Methanol.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Acute toxicity

Acute oral toxicity

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s):

LD50, Rat, > 5,000 mg/kg Estimated.

Page 7 of 17

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s):

LD50, > 2,000 mg/kg Estimated.

Acute inhalation toxicity

Brief exposure (minutes) is not likely to cause adverse effects. Vapor from heated material may cause respiratory irritation.

As product: The LC50 has not been determined.

Skin corrosion/irritation

Prolonged contact may cause slight skin irritation with local redness.

Serious eye damage/eye irritation

May cause severe eye irritation.

May cause corneal injury.

Sensitization

For skin sensitization:

Contains component(s) which have caused allergic skin sensitization in guinea pigs.

Contains component(s) which have demonstrated the potential for contact allergy in mice.

For respiratory sensitization:

No relevant information found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Contains component(s) which have been reported to cause effects on the following organs in animals: Blood.

Respiratory tract.

Carcinogenicity

For this family of materials: Did not cause cancer in long-term animal studies which used routes of exposure considered relevant to industrial handling. Positive results have been reported in other studies using routes of exposure not relevant to industrial handling. During use of the material, small amounts of methylethylketoxime (MEKO) will be released. Rodents exposed to chronic MEKO inhalation throughout their lifetimes showed significant increases in liver tumour rates.

Contains an additional component(s) that is/are encapsulated in the product and are not expected to be released under normal processing conditions or foreseeable emergency.

Teratogenicity

Contains component(s) which caused birth defects in laboratory animals only at doses toxic to the mother.

Reproductive toxicity

Contains component(s) which have been shown to interfere with reproduction in animal studies.

Mutagenicity

Contains a component(s) which were negative in in vitro genetic toxicity studies. Contains component(s) which were negative in animal genetic toxicity studies.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

COMPONENTS INFLUENCING TOXICOLOGY:

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

Acute inhalation toxicity

The LC50 has not been determined.

Vinyltri (methylethylketoxime) silane

Acute inhalation toxicity

The LC50 has not been determined.

N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine

Acute inhalation toxicity

LC50, Rat, 4 Hour, dust/mist, 1.49 - 2.44 mg/l OECD Test Guideline 403

Octamethyl Cyclotetrasiloxane

Acute inhalation toxicity

LC50, Rat, male and female, 4 Hour, dust/mist, 36 mg/l OECD Test Guideline 403

Methyltri(ethylmethylketoxime)silane isomers and oligomers

Acute inhalation toxicity

The LC50 has not been determined.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

Acute inhalation toxicity

The LC50 has not been determined.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

For the hydrolysis product(s)

LC50, Oncorhynchus mykiss (rainbow trout), Static, 96 Hour, > 120 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

For the hydrolysis product(s)

EC50, Daphnia magna (Water flea), static test, 48 Hour, > 120 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

For the hydrolysis product(s)

EC50, Selenastrum capricornutum (green algae), Static, 72 Hour, Growth rate, 94 mg/l, OECD Test Guideline 201

For the hydrolysis product(s)

NOEC, Selenastrum capricornutum (green algae), Static, 72 Hour, Growth rate, 30 mg/l, OECD Test Guideline 201

Chronic toxicity to fish

NOEC, Oryzias latipes (Orange-red killifish), flow-through test, 14 d, 50 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna, semi-static test, 21 d, > 100 mg/l

Vinyltri (methylethylketoxime) silane

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

LC50, Oncorhynchus mykiss (rainbow trout), 96 Hour, > 120 mg/l, OECD Test Guideline 203 LC50, Oryzias latipes (Orange-red killifish), 96 Hour, > 100 mg/l, OECD Test Guideline 203

N-(3-(TrimethoxysilyI) propyI)-1,2-ethanediamine

Acute toxicity to fish

Material is toxic to aquatic organisms (LC50/EC50/IC50 between 1 and 10 mg/L in the most sensitive species).

For the hydrolysis product(s)

LC50, zebra fish (Brachydanio rerio), 96 Hour, 597 mg/l

Acute toxicity to aquatic invertebrates

For the hydrolysis product(s)

EC50, Daphnia magna (Water flea), 48 Hour, 81 mg/l

Acute toxicity to algae/aquatic plants

For the hydrolysis product(s)

ErC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate inhibition, 8.8 mg/l

For the hydrolysis product(s)

NOEC, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate inhibition, 3.1 mg/l

Toxicity to bacteria

For the hydrolysis product(s)

EC50, Pseudomonas putida, 16 Hour, Growth inhibition, 67 mg/l

Chronic toxicity to aquatic invertebrates

For the hydrolysis product(s)

NOEC, Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, > 1 mg/l

Toxicity to Above Ground Organisms

Material is moderately toxic to birds on an acute basis (LD50 between 51 and 500 mg/kg).

Toxicity to soil-dwelling organisms

NOEC, Eisenia fetida (earthworms), 14 d, >= 1,000 mg/kg

Octamethyl Cyclotetrasiloxane

Acute toxicity to fish

Not expected to be acutely toxic to aquatic organisms.

No toxicity at the limit of solubility

LC50, Oncorhynchus mykiss (rainbow trout), flow-through, 96 Hour, > 0.022 mg/l

No toxicity at the limit of solubility

LC50, Cyprinodon variegatus (sheepshead minnow), flow-through, 14 d, > 0.0063 mg/l

Acute toxicity to aquatic invertebrates

No toxicity at the limit of solubility

EC50, Mysidopsis bahia (opossum shrimp), flow-through test, 96 Hour, > 0.0091 mg/l

No toxicity at the limit of solubility

EC50, Daphnia magna (Water flea), flow-through test, 48 Hour, > 0.015 mg/l

Acute toxicity to algae/aquatic plants

No toxicity at the limit of solubility

ErC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate, > 0.022 mg/l

Chronic toxicity to fish

No toxicity at the limit of solubility

NOEC, Oncorhynchus mykiss (rainbow trout), 93 d, >= 0.0044 mg/l

Chronic toxicity to aquatic invertebrates

No toxicity at the limit of solubility

NOEC, Daphnia magna (Water flea), 21 d, >= 0.0079 mg/l

Methyltri(ethylmethylketoxime)silane isomers and oligomers

Acute toxicity to fish

No relevant data found.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

Acute toxicity to fish

Material is slightly toxic to aquatic organisms on an acute basis (LC50/EC50 between 10 and 100 mg/L in the most sensitive species tested).

For similar material(s):

LC50, Zebra fish (Danio/Brachydanio rerio), semi-static test, 96 Hour, > 100 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

For similar material(s):

EC50, Daphnia magna, static test, 48 Hour, 17 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

For similar material(s):

ErC50, Algae (Scenedesmus subspicatus), Growth rate, 72 Hour, Growth rate, 37 mg/l, OECD Test Guideline 201 or Equivalent

For similar material(s):

NOEC, Algae (Scenedesmus subspicatus), Growth rate, 72 Hour, Growth rate, 1.1 mg/l, OECD Test Guideline 201 or Equivalent

Toxicity to bacteria

For similar material(s):

EC50, Bacteria, 3 Hour, Respiration rates., 14 mg/l

Persistence and degradability

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

Biodegradability: Based on information for a similar material: This material rapidly

hydrolyzes to products that are either readily or ultimately biodegradable.

10-day Window: Fail **Biodegradation:** 0 % **Exposure time:** 28 d

Method: OECD Test Guideline 301A

Vinyltri (methylethylketoxime) silane

Biodegradability: Material is expected to biodegrade very slowly (in the environment). Fails

to pass OECD/EEC tests for ready biodegradability.

10-day Window: Fail **Biodegradation:** 0 % **Exposure time:** 28 d

Method: OECD Test Guideline 301A

Stability in Water (1/2-life)

, DT50, < 1 min, Half-life Temperature 2 °C, OECD Test Guideline 111

N-(3-(TrimethoxysilyI) propyI)-1,2-ethanediamine

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Fail **Biodegradation:** 39 % **Exposure time:** 28 d

Method: OECD Test Guideline 301A or Equivalent

Theoretical Oxygen Demand: 2.39 mg/mg Estimated.

Chemical Oxygen Demand: 1.76 mg/mg Estimated.

Biological oxygen demand (BOD)

Incubation Time	BOD
5 d	23 %
10 d	30 %
20 d	29 %

Stability in Water (1/2-life)

Hydrolysis, half-life, 0.025 Hour, pH 7

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitization: OH radicals **Atmospheric half-life:** 0.088 d

Method: Estimated.

Octamethyl Cyclotetrasiloxane

Biodegradability: Material is expected to biodegrade very slowly (in the environment). Fails

Issue Date: 08/30/2019

to pass OECD/EEC tests for ready biodegradability.

10-day Window: Not applicable **Biodegradation:** 3.7 % **Exposure time:** 28 d

Method: OECD Test Guideline 310

Stability in Water (1/2-life)

Hydrolysis, DT50, 69.3 - 144 Hour, pH 7, Half-life Temperature 24.6 °C, OECD Test Guideline 111

Photodegradation

Atmospheric half-life: 16 d

Method: Estimated.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

Biodegradability: No relevant data found.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

Biodegradability: For similar material(s): Material is expected to biodegrade very slowly (in

the environment). Fails to pass OECD/EEC tests for ready biodegradability.

For similar material(s): 10-day Window: Fail

Biodegradation: 3 % **Exposure time:** 28 d

Method: OECD Test Guideline 301F or Equivalent

Bioaccumulative potential

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

Bioaccumulation: Bioconcentration potential is low (BCF less than 100 or log Pow greater

than 7).

Partition coefficient: n-octanol/water(log Pow): 11.2

Vinyltri (methylethylketoxime) silane

Bioaccumulation: No relevant data found.

N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): < 3 estimated

Octamethyl Cyclotetrasiloxane

Bioaccumulation: Bioconcentration potential is high (BCF > 3000 or Log Pow between 5 and

Partition coefficient: n-octanol/water(log Pow): 6.49 Measured

Bioconcentration factor (BCF): 12,400 Pimephales promelas (fathead minnow) Measured

Methyltri(ethylmethylketoxime)silane isomers and oligomers

Bioaccumulation: No relevant data found.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

Bioaccumulation: No relevant data found.

Mobility in soil

Page 13 of 17

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

No relevant data found.

Vinyltri (methylethylketoxime) silane

No relevant data found.

N-(3-(TrimethoxysilyI) propyI)-1,2-ethanediamine

Expected to be relatively immobile in soil (Koc > 5000).

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

Partition coefficient (Koc): > 5000 Estimated.

Octamethyl Cyclotetrasiloxane

Expected to be relatively immobile in soil (Koc > 5000).

Methyltri(ethylmethylketoxime)silane isomers and oligomers

No relevant data found.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

No relevant data found.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

Treatment and disposal methods of used packaging: Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

14. TRANSPORT INFORMATION

DOT

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

Not regulated for transport

Transport in bulk Consult IMO regulations before transporting ocean bulk

Page 14 of 17

according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Serious eye damage or eye irritation

Respiratory or skin sensitisation

Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103

Calculated RQ exceeds reasonably attainable upper limit.

Components	CASRN	RQ (RCRA Code)
Methanol	67-56-1	5000 lbs RQ
Methanol	67-56-1	100 lbs RQ (F003)
Hexane	110-54-3	5000 lbs RQ

Pennsylvania Right To Know

The following chemicals are listed because of the additional requirements of Pennsylvania law:

Components	CASRN
Polydimethylsiloxane hydroxy-terminated	70131-67-8
Siloxanes and silicones, dimethyl	63148-62-9
Silicon dioxide	7631-86-9
2-Butanone, O,O',O"-(methylsilylidyne)trioxime	22984-54-9
Cobalt titanite green spinel	68186-85-6
Aluminium	7429-90-5

California Prop. 65

WARNING: This product can expose you to chemicals including Cobalt titanite green spinel, which is/are known to the State of California to cause cancer, and Hexane, Methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Hazard Rating System

NFPA

	Health	Flammability	Instability
	2	1	0
H	MIS		
	Health	Elammability	Physical

Health	Flammability	Physical Hazard
2*	1	0

^{* =} Chronic Effects (See Hazards Identification)

Revision

Identification Number: 4100223 / A001 / Issue Date: 08/30/2019 / Version: 11.0 Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

USA. ACGIH Threshold Limit Values (TLV)
ACGIH - Biological Exposure Indices (BEI)
Dow Industrial Hygiene Guideline
USA. NIOSH Recommended Exposure Limits
USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air
Contaminants
Short-term exposure limit
Time weighted average
USA. Workplace Environmental Exposure Levels (WEEL)

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of

Page 16 of 17

Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization: KECI - Korea Existing Chemicals Inventory: LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose): MARPOL - International Convention for the Prevention of Pollution from Ships: MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA -Resource Conservation and Recovery Act: REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA -Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

THE DOW CHEMICAL COMPANY urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.