3.5%

0.6%

### Material Safety Data Sheet acc. to ISO/DIS 11014

Printing Date 11/24/2008

ROYA

**Revision Number 3** 

Reviewed on 06/23/2004

**1 Identification of substance** 

· Product details

· Trade name: DC12154 GUNTHER PREMIER

**GUNTHER** 

MIRROR

· Article number: 12154MM

 Manufacturer/Supplier: Gunther Mirror Mastic
Royal Adhesives And Sealants, LLC
2001 W. Washington Street
South Bend IN 46628-2023

· Information department: Environment protection department.

· Emergency information: ChemTrec: UNITED STATES 1(800)424-9300 INTERNATIONAL 202-483-7616

#### 2 Composition/Data on components

· Chemical characterization

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

1330-20-7 xylene

101-68-8 4,4'-methylenediphenyl diisocyanate

· Additional information: For the wording of the listed risk phrases refer to section 15.

### **3 Hazards identification**

• Hazard description:

Harmful

· Information pertaining to particular dangers for man and environment:

May cause sensitisation by inhalation.

Contains isocyanates. See information supplied by the manufacturer.

Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)

HEALTH1Health = 1FIRE2Fire = 2PHYSICAL HAZARD1Physical Hazard = 1

### 4 First aid measures

· After inhalation: Supply fresh air; consult doctor in case of complaints.

• After skin contact: Wash contaminated skin with soap and water.

· After eye contact: Rinse opened eye for several minutes under running water.

USA

# Material Safety Data Sheet acc. to ISO/DIS 11014

Printing Date 11/24/2008

Revision Number 3

Reviewed on 06/23/2004

Trade name: DC12154 GUNTHER PREMIER

(Contd. of page 1)

· After swallowing: Call a doctor immediately.

### **5** Fire fighting measures

- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Protective equipment: Wear self-contained respiatory protective device.

### 6 Accidental release measures

- · Person-related safety precautions: Keep away from ignition sources
- *Measures for environmental protection:* Do not allow to enter sewers/ surface or ground water. • *Measures for cleaning/collecting:*

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of contaminated material as waste in accordance with federal state and local regulations. Ensure adequate ventilation.

### 7 Handling and storage

- · Handling:
- · Information for safe handling: Ensure good ventilation/exhaustion at the workplace.
- · Information about protection against explosions and fires: Keep ignition sources away Do not smoke.
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location away from direct heat.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.

### 8 Exposure controls and personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Components with limit values that require monitoring at the workplace:

#### 1330-20-7 xylene

PEL 435 mg/m<sup>3</sup>, 100 ppm

- REL Short-term value: 655 mg/m<sup>3</sup>, 150 ppm Long-term value: 435 mg/m<sup>3</sup>, 100 ppm
- TLV Short-term value: 435 mg/m<sup>3</sup>, 100 ppm Long-term value: 434 mg/m<sup>3</sup>, 100 ppm BEI

#### 101-68-8 4,4'-methylenediphenyl diisocyanate

- PEL Short-term value: C 0.2 mg/m<sup>3</sup>, C 0.02 ppm
- REL Short-term value: C 0.2\* mg/m<sup>3</sup>, C 0.02\* ppm Long-term value: 0.05 mg/m<sup>3</sup>, 0.005 ppm \*10-min
- *TLV* 0.051 mg/m<sup>3</sup>, 0.005 ppm

• Additional information: The lists that were valid during the creation were used as basis.

#### · Personal protective equipment (see listings below)

• General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.

(Contd. on page 3)

USA

### Material Safety Data Sheet acc. to ISO/DIS 11014

Printing Date 11/24/2008

Revision Number 3

Reviewed on 06/23/2004

(Contd. of page 2)

#### Trade name: DC12154 GUNTHER PREMIER

#### · Breathing equipment:

In the absence of adequate ventilation, NIOSH-certified respiratory protection for organic vapor should be used as necessary. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- · Protection of hands: Protective gloves
- Eye protection: Safety glasses with side shields.
- · Body protection: Protective work clothing

### 9 Physical and chemical properties

· General Information		
Form:	Paste	
Color:	Gray	
Odor:	Characteristic	
· Change in condition		
Melting point:	Undetermined.	
<b>Boiling point:</b>	Undetermined.	
· Flash point:	58°C (136°F)	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Specific gravity:	1.170	
· Solubility in / Miscibility w	rith	
Water:	Not miscible or difficult to mix.	
· Solvent content:		
Organic solvents:	3.5 %	
· Solids content:	96.5 %	
· Additional information:	VOC: = 74  G/L	
	WEIGHT PER GALLON: = 11.42	

## **10 Stability and reactivity**

• *Thermal decomposition / conditions to be avoided:* No decomposition if used according to specifications. • *Dangerous reactions* No dangerous reactions known.

• **Dangerous products of decomposition:** Oxides of carbon and nitrogen. Isocyanate

# **11 Toxicological information**

· Acute toxicity:

 $\cdot$  LD/LC50 values that are relevant for classification:

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral LD50 2200 mg/kg (mouse)

· Primary irritant effect:

• on the skin: Generally this product does not irritate the skin.

(Contd. on page 4)

USA

### Material Safety Data Sheet acc. to ISO/DIS 11014

Printing Date 11/24/2008

Revision Number 3

Reviewed on 06/23/2004

#### Trade name: DC12154 GUNTHER PREMIER

• on the eye: Irritating effect.

· Sensitization: Sensitization possible through inhalation.

· Additional toxicological information:

*The product shows the following dangers according to internally approved calculation methods for preparations: Harmful* 

# **12** Ecological information

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

### **13 Disposal considerations**

- · Product:
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

### **14 Transport information**

- · DOT regulations:
- · Hazard class: NON REGULATED
- · Maritime transport IMDG:
- Marine pollutant: .

# **15 Regulations**

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

1330-20-7 xylene

101-68-8 4,4'-methylenediphenyl diisocyanate

· TSCA (Toxic Substances Control Act):

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity:

None of the ingredients is listed.

#### · Cancerogenity categories

· EPA (Environmental Protection Agency)

1330-20-7 xylene

D

(Contd. of page 3)

USA

### Material Safety Data Sheet acc. to ISO/DIS 11014

Printing Date 11/24/2008

Revision Number 3

Reviewed on 06/23/2004

Trade name: DC12154 GUNTHER PREMIER

	(Contd. of page 4)	
101-68-8 4,4'-methylenediphenyl diisocyanate	CBD;D	
· IARC (International Agency for Research on Cancer)		
1330-20-7 xylene	3	
101-68-8 4,4'-methylenediphenyl diisocyanate	3	
· NTP (National Toxicology Program)		
None of the ingredients is listed.		
· TLV (Threshold Limit Value established by ACGIH)		
1330-20-7 xylene	A4	
· MAK (German Maximum Workplace Concentration)		
101-68-8 4,4'-methylenediphenyl diisocyanate	3	
· NIOSH-Ca (National Institute for Occupational Safety and Health)		
None of the ingredients is listed.		
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

· Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

- *Hazard-determining components of labelling:* 4,4'-methylenediphenyl diisocyanate
- *Risk phrases: May cause sensitisation by inhalation.*
- *Special labeling of certain preparations:* Contains isocyanates. See information supplied by the manufacturer.
- · National regulations:
- Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

# **16 Other information**

Although the information and recommendations set forth in this MSDS are presented in good faith and are believed to be correct as of the date of this MSDS, Royal Adhesives & Sealants makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the MSDS.

· Department issuing MSDS: Environment protection department.