

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC FC BUFF
Material: 960807 323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Cleveland OH 44122
US

Contact person: EH&S Department
Telephone: 216-292-5000
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Carcinogenicity	Category 1A
Toxic to reproduction	Category 1B

Unknown toxicity - Health

Acute toxicity, oral	10.19 %
Acute toxicity, dermal	12.51 %
Acute toxicity, inhalation, vapor	99.62 %
Acute toxicity, inhalation, dust or mist	99.95 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 1
--	------------

Unknown toxicity - Environment

Acute hazards to the aquatic environment	43.34 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: May cause cancer.
May damage fertility or the unborn child.
Very toxic to aquatic life.

Precautionary Statement:

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.

Response: If exposed or concerned: Get medical advice/attention. Collect spillage.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Other hazards which do not result in GHS classification: None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	30 - 60%
Butyl benzyl phthalate	85-68-7	15 - 40%
Calcium Carbonate (Limestone)	1317-65-3	7 - 13%
Calcium oxide	1305-78-8	1 - 5%
Titanium dioxide	13463-67-7	0.5 - 1.5%
Stearic acid	57-11-4	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.

Inhalation: Move to fresh air.

Skin Contact: Wash skin thoroughly with soap and water. If skin irritation occurs: Get medical advice/attention.

Eye contact: Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: No data available.

Methods and material for containment and cleaning up: Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling: Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities: Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m ³	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m ³	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m ³	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m ³	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Diisodecyl phthalate	TWAEV	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Vinyltrimethoxysilane	STEL	10 ppm 60 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)

Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

- General information:** Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
- Eye/face protection:** Wear safety glasses with side shields (or goggles).
- Skin Protection**
- Hand Protection:** Use suitable protective gloves if risk of skin contact.
- Other:** Wear suitable protective clothing.
- Respiratory Protection:** In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
- Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use.

9. Physical and chemical properties

Appearance

- Physical state:** solid
- Form:** Paste
- Color:** Tan
- Odor:** Mild
- Odor threshold:** No data available.
- pH:** No data available.
- Melting point/freezing point:** No data available.
- Initial boiling point and boiling range:** No data available.

Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.5225
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects**Acute toxicity (list all possible routes of exposure)****Oral****Product:** ATEmix: 82,883.72 mg/kg**Dermal****Product:** ATEmix: 4,433.55 mg/kg**Inhalation****Product:** No data available.**Repeated dose toxicity****Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Butyl benzyl phthalate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating

Respiratory or Skin Sensitization**Product:** No data available.**Carcinogenicity****Product:** No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.
--	-------------------------------

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity

Product: May damage fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information**Ecotoxicity:****Acute hazards to the aquatic environment:**

Fish Product:	No data available.
Specified substance(s): Calcium carbonate	LC 50 (Western mosquitofish (<i>Gambusia affinis</i>), 96 h): > 56,000 mg/l Mortality
Butyl benzyl phthalate	LC 50 (Fathead minnow (<i>Pimephales promelas</i>), 96 h): 1.39 - 3.88 mg/l

Mortality

Titanium dioxide LC 50 (Mummichog (*Fundulus heteroclitus*), 96 h): > 1,000 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Butyl benzyl phthalate EC 50 (Water flea (*Daphnia magna*), 48 h): > 10 mg/l Intoxication
 EC 50 (Opossum shrimp (*Americamysis bahia*), 48 h): > 0.9 mg/l Mortality
 EC 50 (Water flea (*Daphnia magna*), 24 h): > 10 mg/l Intoxication
 EC 50 (Water flea (*Daphnia magna*), 21 d): > 0.76 mg/l Intoxication
 EC 50 (Water flea (*Daphnia magna*), 14 d): > 0.76 mg/l Intoxication

Titanium dioxide EC 50 (Water flea (*Daphnia magna*), 48 h): > 1,000 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Butyl benzyl phthalate NOAEL (*Pimephales promelas*, 126 d): 64.6 - 67.5 µg/l experimental result

Calcium oxide NOAEL (*Oncorhynchus mykiss*, 60 d): 307 mg/l interpreted

Titanium dioxide LC 0 (*Coregonus autumnalis migratorius* G., 30 d): 3 mg/l experimental result

Hydrotreated heavy naphthenic distillate NOAEL (*Oncorhynchus mykiss*, 14 d): >= 1,000 mg/l QSAR

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

Butyl benzyl phthalate Bluegill (*Lepomis macrochirus*), Bioconcentration Factor (BCF): 772 (Flow through)

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Butyl benzyl phthalate Log Kow: 4.91

Stearic acid Log Kow: 8.23

Mobility in Soil: No data available.

Other Adverse Effects: Very toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Butyl Benzyl Phthalate), 9, PG III, MARINE POLLUTANT

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Butyl benzyl phthalate	100 lbs.
Dibutyl phthalate	10 lbs.
Methanol	5000 lbs.
Acetic acid	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories**

Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Butyl benzyl phthalate	100 lbs.
Diisodecyl phthalate	
Dibutyl phthalate	10 lbs.
Diisodecyl phthalate (mixed Is)	
Methanol	5000 lbs.
Acetic acid	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Calcium carbonate	500 lbs
Butyl benzyl phthalate	500 lbs
Calcium Carbonate (Limestone)	500 lbs
Calcium oxide	500 lbs
Titanium dioxide	500 lbs
Stearic acid	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Calcium carbonate
Butyl benzyl phthalate
Calcium Carbonate (Limestone)
Calcium oxide
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List

Chemical Identity

Calcium carbonate
Butyl benzyl phthalate
Calcium Carbonate (Limestone)
Calcium oxide
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Calcium carbonate
Butyl benzyl phthalate
Calcium Carbonate (Limestone)
Diisodecyl phthalate
Calcium oxide

US. Rhode Island RTK

Chemical Identity

Butyl benzyl phthalate
Diisodecyl phthalate

Other Regulations:

Regulatory VOC (less water and exempt solvent):	6 g/l
VOC Method 310:	0.39 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.

Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision
--

Revision Date:	11/23/2015
Version #:	1.0
Further Information:	No data available.
Disclaimer:	For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

