

# SAFETY DATA SHEET

## 1. Identification

## Material name: TREMSIL 600 BLACK Material: 944802 323

## Recommended use and restriction on use

Recommended use: Sealant Restrictions on use: Not known.

## Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants 3735 Green Road Beachwood OH 44122 US

Contact person: Telephone: Emergency telephone number: EH&S Department 216-292-5000 1-800-424-9300 (US); 1-613-996-6666 (Canada)

## 2. Hazard(s) identification

## Hazard Classification

## Health Hazards

Carcinogenicity

Category 2

## Unknown toxicity - Health

Acute toxicity, oral	49.97 %
Acute toxicity, dermal	51.4 %
Acute toxicity, inhalation, vapor	99.94 %
Acute toxicity, inhalation, dust or mist	98.92 %

## Label Elements

## Hazard Symbol:



Signal Word:

Precautionary

Warning

Hazard Statement:

Suspected of causing cancer.



Statements	
Prevention:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	IF exposed or concerned: Get medical advice/attention.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	None.

## 3. Composition/information on ingredients

## **Mixtures**

Chemical Identity	CAS number	Content in percent (%)*
Calcium Carbonate (Limestone)	1317-65-3	20 - <50%
Polydimethylsiloxane, trimethyl endcap	63148-62-9	5 - <10%
Amorphous silica	7631-86-9	1 - <5%
Aminosilane	919-30-2	1 - <5%
Hexamethyldisilazane	999-97-3	0.1 - <1%
Carbon Black	1333-86-4	0.1 - <1%

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

## 4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.	
Inhalation:	Move to fresh air.	
Skin Contact:	Wash skin thoroughly with soap and water. If skin irritation occurs: Get medical advice/attention.	
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.	
Most important symptoms/effect	ts, acute and delayed	
Symptoms:	May cause skin and eye irritation.	
Indication of immediate medical attention and special treatment needed		

Treatment: Symptoms may be delayed.



## 5. Fire-fighting measures

General Fire Hazards:	No unusual fire or explosion hazards noted.
Contrar i no mazarao.	

## Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical:	During fire, gases hazardous to health may be formed.
Special protective equipment an	d precautions for firefighters
Special fire fighting procedures:	No data available.
Special protective equipment	Self-contained breathing apparatus and full protective clothing must be

## for fire-fighters: worn in case of fire.

6. Accidental release measures		
Personal precautions, protective equipment and emergency procedures:	No data available.	
Methods and material for containment and cleaning up:	Collect spillage in containers, seal securely and deliver for disposal according to local regulations.	
Notification Procedures:	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.	
Environmental Precautions:	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer. Environmental manager must be informed of all major spillages.	
7. Handling and storage		
Precautions for safe handling:	Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety	

precautions have been read and understood. Obtain special instructions

before use. Use personal protective equipment as required.

## Conditions for safe storage, Store locked up. including any incompatibilities:



## 8. Exposure controls/personal protection

## **Control Parameters**

## **Occupational Exposure Limits**

Chemical Identity	Туре	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Amorphous silica	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.8 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (2011)
Carbon Black	PEL	3.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	Туре	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)



Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Amorphous silica - Total	TWA	4 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable.	TWA	1.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable dust.	TWA	6 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Carbon Black - Inhalable	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Carbon Black	TWA	3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Chemical name	Туре	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)



Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupation Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Wor Environment) (09 2017)
Amorphous silica - Total	TWA	4 mg/m3	Canada. British Columbia OELs. (Occupation Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable.	TWA	1.5 mg/m3	Canada. British Columbia OELs. (Occupation Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable dust.	TWA	6 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Wor Environment) (09 2017)
Carbon Black - Inhalable	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupation Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure Biological or Chemical Agents) (06 2015)
Carbon Black	TWA	3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Wor Environment) (09 2017)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupation Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure Biological or Chemical Agents) (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Wor Environment) (09 2017)
Cyclohexane	TWA	100 ppm	Canada. British Columbia OELs. (Occupation Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Cyclohexane	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure Biological or Chemical Agents) (11 2010)
Cyclohexane	TWA	300 ppm 1,030 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Wor Environment) (12 2008)
Dibutyltin diacetate - as Sn	STEL	0.2 mg/m3	Canada. British Columbia OELs. (Occupation Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.1 mg/m3	Canada. British Columbia OELs. (Occupation Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Dibutyltin diacetate - as Sn	TWA	0.1 mg/m3	Canada. Ontario OELs. (Control of Exposure Biological or Chemical Agents) (11 2010)
Dibutyltin diacetate - as Sn	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Wor Environment) (09 2017)
	STEL	0.2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Wor Environment) (09 2017)



Ethyl alcohol	STEL	1,000 ppm		Canada. British Columbia OELs. (Occupationa Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Ethyl alcohol	STEL	1,000 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethyl alcohol	TWA	1,000 ppm	1,880 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Toluene	TWA	20 ppm		Canada. British Columbia OELs. (Occupationa Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Toluene	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Toluene	TWA	50 ppm	188 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Acetic acid	STEL	15 ppm		Canada. British Columbia OELs. (Occupationa Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 ppm		Canada. British Columbia OELs. (Occupationa Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Acetic acid	STEL	15 ppm		Canada. Ontario OELs. (Control of Exposure t Biological or Chemical Agents) (11 2010)
	TWA	10 ppm		Canada. Ontario OELs. (Control of Exposure t Biological or Chemical Agents) (11 2010)
Acetic acid	TWA	10 ppm	25 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	STEL	15 ppm	37 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

#### Appropriate Engineerin Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

## Individual protection measures, such as personal protective equipment

General information:	Use personal protective equipment as required.
Eye/face protection:	Wear goggles/face shield.
Skin Protection Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	No data available.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product.

## 9. Physical and chemical properties



Appearance	
Physical state:	solid
Form:	Paste
Color:	Black
Odor:	Mild sharp
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explo	sive limits
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.37
Solubility(ies)	
Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.
10. Stability and reactivity	

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.



11. Toxicological information		
Information on likely routes of e Inhalation:	exposure In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.	
Skin Contact:	Causes mild skin irritation.	
Eye contact:	Eye contact is possible and should be avoided.	
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.	
Symptoms related to the physic	cal, chemical and toxicological characteristics	
Inhalation:	No data available.	
Skin Contact:	No data available.	
Eye contact:	No data available.	
Ingestion:	No data available.	
Information on toxicological eff	fects	
Acute toxicity (list all possible routes of exposure)		
Oral Product:	ATEmix: 88,837.55 mg/kg	
Dermal Product:	ATEmix: 42,688.14 mg/kg	
Inhalation Product:	Not classified for acute toxicity based on available data.	
Specified substance(s): Amorphous silica	LC 50 (Rat): > 2.08 mg/l	
Aminosilane	LC 50 (Rat): > 7.35 mg/l	
Hexamethyldisilazane	LC 50 (Rat): 8,700 mg/m3	
Repeated dose toxicity Product:	No data available.	
Skin Corrosion/Irritation Product:	No data available.	



Specified substance(s): Amorphous silica	in vivo (Rabbit): Not irritant Experimental result, Key study
Aminosilane	in vivo (Rabbit): Highly irritating Experimental result, Supporting study
Hexamethyldisilazane	Irritating in vivo (Rabbit): Not irritant Experimental result, Weight of Evidence study
Carbon Black	in vivo (Rabbit): Not irritant Experimental result, Key study

#### Serious Eye Damage/Eye Irritation

Product: Specified substance(s):	No data available.
Amorphous silica	Rabbit, 24 hrs: Not irritating
Aminosilane	Rabbit, 24 - 72 hrs: Highly irritating
Hexamethyldisilazane	Rabbit, 24 - 72 hrs: Not irritating
Carbon Black	Rabbit, 24 - 72 hrs: Not irritating

## **Respiratory or Skin Sensitization**

Product:	No data available.
i louuot.	

#### Carcinogenicity Product:

Suspected of causing cancer.

## IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Carbon Black Overall evaluation: Possibly carcinogenic to humans.

## US. National Toxicology Program (NTP) Report on Carcinogens: No carcinogenic components identified

## US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): No carcinogenic components identified

## **Germ Cell Mutagenicity**

In vitro	
Product:	No data available.

In vivo Product:

No data available.

## Reproductive toxicity Product:

No data available.



Specific Target Organ Toxicity	<b>y - Single Exposure</b>
Product:	No data available.
Specific Target Organ Toxicity	y - Repeated Exposure
Product:	No data available.
Aspiration Hazard Product:	No data available.
Other effects:	No data available.

## 12. Ecological information

## Ecotoxicity:

## Acute hazards to the aquatic environment:

Fish Product:	No data available.	
Specified substance(s): Polydimethylsiloxane, trimethyl endcap	LC 50 (Redear sunfish (Lepomis microlophus), 96 h): 26.27 - 56.73 mg/l Mortality	
Aquatic Invertebrates Product:	No data available.	
Specified substance(s): Polydimethylsiloxane, trimethyl endcap	LC 50 (Water flea (Daphnia magna), 48 h): 44.5 mg/l Mortality	
Chronic hazards to the aquatic environment:		
Fish Product:	No data available.	
Aquatic Invertebrates Product:	No data available.	
Toxicity to Aquatic Plants Product:	No data available.	
Persistence and Degradability		



Biodegradation Product:	No data available.
BOD/COD Ratio Product:	No data available.
Bioaccumulative potential Bioconcentration Factor (BC Product:	CF) No data available.
Partition Coefficient n-octanol / v Product:	vater (log Kow) No data available.
Specified substance(s): Hexamethyldisilazane	Log Kow: 2.62
Mobility in soil:	No data available.
Other adverse effects:	No data available.
13. Disposal considerations	
Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.
14. Transport information	
TDG:	
Not Regulated	

## CFR / DOT:

Not Regulated

## IMDG:

Not Regulated

## 15. Regulatory information

## **US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)



None present or none present in regulated quantities.

## US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

#### Chemical Identity

## OSHA hazard(s)

Crystalline Silica	
(Quartz)/ Silica Sand	

#### kidney effects lung effects immune system effects

Cancer

## CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	
Cyclohexane	

## Reportable quantity 1000 lbs.

Cyclonexane	1000 lbs.
Ethyl alcohol	100 lbs.
Toluene	1000 lbs.
Acetic acid	5000 lbs.

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

## **Hazard categories**

Delayed (Chronic) Health Hazard Carcinogenicity

#### SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

## SARA 304 Emergency Release Notification

Chemical Identity	<b>Reportable quantity</b>
Cyclohexane	1000 lbs.
Ethyl alcohol	100 lbs.
Toluene	1000 lbs.
Acetic acid	5000 lbs.

## SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Calcium Carbonate	10000 lbs
(Limestone)	
Polydimethylsiloxane,	10000 lbs
trimethyl endcap	
Amorphous silica	10000 lbs
Aminosilane	10000 lbs
Hexamethyldisilazane	10000 lbs
Carbon Black	10000 lbs

## SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) None present or none present in regulated quantities.

## Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.



## **US State Regulations**

## **US. California Proposition 65**



#### WARNING

Cancer and Reproductive Harm - www.P65Warnings.ca.gov

## US. New Jersey Worker and Community Right-to-Know Act

<u>Chemical Identity</u> Calcium Carbonate (Limestone) Amorphous silica Carbon Black

#### **US. Massachusetts RTK - Substance List**

Chemical Identity

Calcium Carbonate (Limestone) Amorphous silica Crystalline Silica (Quartz)/ Silica Sand

## US. Pennsylvania RTK - Hazardous Substances

<u>Chemical Identity</u> Calcium Carbonate (Limestone) Amorphous silica

## US. Rhode Island RTK

<u>Chemical Identity</u> Calcium Carbonate (Limestone)

## International regulations

#### Montreal protocol

Not applicable

## Stockholm convention

Not applicable

## **Rotterdam convention**

Not applicable

## Kyoto protocol

Not applicable

## VOC:

Regulatory VOC (less water and exempt solvent)	:	35 g/l
VOC Method 310	:	2.57 %



Inventory Status: Canada DSL Inventory List:

EINECS, ELINCS or NLP:

Japan (ENCS) List:

Canada NDSL Inventory:

US TSCA Inventory:

New Zealand Inventory of Chemicals:

Japan ISHL Listing:

Japan Pharmacopoeia Listing:

Australia AICS:

China Inv. Existing Chemical Substances:

Korea Existing Chemicals Inv. (KECI):

Philippines PICCS:

Mexico INSQ:

Ontario Inventory:

Taiwan Chemical Substance Inventory:

All components in this product are listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

All components in this product are listed on or exempt from the Inventory.

All components in this product are listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.



## 16.Other information, including date of preparation or last revision

Revision Date:	11/30/2018
Version #:	1.1
Further Information:	No data available.
Disclaimer:	For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.